

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A radio communication device, comprising:
 - a metallized housing;
 - an antenna coupled to the metallized housing; and
 - the metallized housing includes an antenna bandwidth enhancing slot that directs existing electrical currents flowing in the metallized housing to take different paths to at least increase the bandwidth of the antenna by introducing multiple resonances.
2. (original) A radio communication device as defined in claim 1, wherein the metallized housing includes a flip section that can be placed in an open or closed position.
3. (original) A radio communication device as defined in claim 2, wherein the antenna bandwidth enhancing slot is located on the flip section.
4. (original) A radio communication device as defined in claim 1, wherein the antenna bandwidth enhancing slot comprises a substantially “L” shaped slot.
5. (original) A radio communication device as defined in claim 4, wherein the “L” shaped slot includes a slot extension.

6. (previously presented) A radio communication device as defined in claim 1, wherein the different paths have different lengths.
7. (original) A radio communication device as defined in claim 6, wherein the antenna comprises a helical and whip combination.
8. (original) A radio communication device as defined in 6, wherein the antenna is electrically coupled to the metallized housing which is grounded.
9. (original) A radio communication device as defined in 1, wherein the radio communication device comprises a cellular telephone.

10. (currently amended) A method for increasing the antenna bandwidth of an antenna found in a radio communication device, comprising the steps of:
 providing a metallized housing for the radio communication device; and
 placing a slot on the metallized housing in order to direct existing electrical currents flowing in the metallized housing to take different paths having different lengths in order to at least increase the bandwidth of the antenna by introducing multiple resonances.
11. (original) A method as defined in claim 10, wherein the slot placed on the metallized housing comprises a substantially “L” shaped slot.
12. (original) A method as defined in claim 11, wherein the “L” shaped slot includes a slot extension.
13. (original) A method as defined in claim 10, wherein the radio communication device comprises a cellular telephone and the metallized housing includes a flip section that can move between an open position and a closed position.
14. (original) A method as defined in claim 13, wherein the slot is located on the flip section.
15. (original) A method as defined in claim 14, wherein a portion of the antenna is located external to the metallized housing.

16. (currently amended) A cellular telephone, comprising:
- an antenna;
 - a metallized housing coupled to the antenna and having a movable section that can be placed in an open or closed position; and
 - a slot located on the movable section, the slot causing any surface currents found on the metallized housing during operation of the antenna to take different electrical paths having different lengths such that multiple resonances are introduced.
17. (original) A cellular telephone as defined in claim 16, wherein the slot at least increases the bandwidth of the antenna.
18. (original) A cellular telephone as defined in claim 17, wherein the slot comprises a substantially “L” shaped slot.
19. (original) A cellular telephone as defined in claim 16, wherein the slot allows for at least two electrical paths for the surface currents to take.
20. (original) A cellular telephone as defined in claim 18, wherein the “L” shaped slot has a short arm and a long arm and the short arm is located along the long arm’s length in such a location along the length of the long arm that dual tuning of the antenna bandwidth can be achieved.

21. (currently amended) A radio communication device, comprising:
- a electrically conductive housing;
 - an antenna coupled to the conductive housing; and
 - the conductive housing includes a slot that enhances the bandwidth of the antenna by directing existing electrical currents flowing in the metallized housing to take different paths such that multiple resonances are introduced.
22. (currently amended) A radio communication device as defined in claim 21, wherein the different paths ~~having~~ have different lengths.
23. (original) A radio communication device as defined in claim 22, wherein the different lengths the electrical currents have to take results in broader bandwidth for the antenna.